

CIRCUIT BREAKERS

Retail Part No.	Bulk Part No.	Fig. No.	Amps 125/250 VAC/32VDC	Actuator	Mounting Hole	Hardware	Spec Drawing Page No.
35-2103	35-2103-BU	1	3	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2104	35-2104-BU	1	4	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2105	35-2105-BU	1	5	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2106	35-2106-BU	1	6	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2107	35-2107-BU	1	7	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2108	35-2108-BU	1	8	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2110	35-2110-BU	1	10	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2112	35-2112-BU	1	12	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2115	35-2115-BU	1	15	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2120	35-2120-BU	1	20	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2125	35-2125-BU	1	25	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2130	35-2130-BU	1	30	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2135	35-2135-BU	1	35	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A
35-2140	35-2140-BU	1	40	Black Plastic Button	0.450"	Nut, Knurling Nut; ID Plate	303-A



Fig. 1

Note: See bottom for Boot (Fig.20)

SPECIALITY SWITCHES



Fig. 2



Fig. 3



Fig. 4



Fig. 10



Fig. 8



Fig. 14

Retail Part No.	Bulk Part No.	Circuit Function	Poles & Throws	Amps 125 VAC	Amps 250 VAC	Actuator	Terminal Style	Body Color	Spec Drawing Page No.
35-864	35-864-BU	2 On Off	SPST	6	3	3-1/2" Pull Chain	6" Wire Leads		303-B
35-865	35-865-BU	3 Off 1-On 2-On	SPDT^	6	3	3-15/16" Pull Chain	Push-in	Purple	303-C
35-867	35-867-BU	3 Off 1-On 2-On 3-On	SP3T	6	3	3-3/4" Pull Chain	Push-in	White	303-D
35-849	35-849-BU	4 On Off	SPST	6	3	Thumbwheel	Insulation Piercing	White Plastic	303-E

Retail Part No.	Bulk Part No.	Action	Poles & Throws	Amps 120 VAC	AMPS 100 VDC	Actuator	Terminal Type	Mounting Type	Gap	Spec Drawing Page No.	
35-750	35-750-BU	8 NO w/o Magnet	SPST	0.5	0.25 **	Magnet Incl.	Screw	Surface	1.18"	303-H	
35-756	35-756-BU	8 NO or NC	SPDT	5W	0.280	0.250	Magnet Incl.	Screw	Surface	1.18"	303-H

Retail Part No.	Bulk Part No.	Action	Poles & Throws	Amps 30 VAC	Watts 30 VDC	Actuator	Terminal Type	Mounting Type	Gap	Spec Drawing Page No.
35-754		10 NO w/o magnet	SPST	0.3	3	Magnet Incl.	Side WL	Submin. Surface	1.000"	303-J

Retail Part No.	Bulk Part No.	Action	Poles & Throws	Amps 6 VDC	Amps 125 VAC	Tilt Angle	Actuator	Terminal Type	Mounting Type	Mounting Holes	Spec Drawing Page No.
35-764	35-764-BU	14 NO or NC	SPST		1/2	15°	Int. Metal Ball	Leads			303-N

Notes: *Rated 6Amps@120VAC ^=3 Position WL= Wire Lead(s) Int.=Internal > 0.3A @ 50Vac ***Rated 0.01A 120VAC, 450mA 1.5VDC, 20mA 50VDC
 **100VDC Incl.=Included †=0.2 Amps@120VDC Max., 4 Watts max. NO/NC=Normally Open or Normally Closed
 Sd=Solder **35-755** contains switch, magnet & coil form. **35-757-BU** contains switch only ††=Ampere turns=15-90

SWITCH ACCESSORIES

Retail Part No.	Bulk Part No.	Fig. No.	Description
35-060	35-060-BU	15	Bat Handle Toggle Switch Boot--Thread size: 15/32-32. (see p.303-O)
	35-061-BU	17	Standard On/Off Switch ID Plate Fits 15/32 bushings
35-436		18	Pushbutton Caps--1 each Red and Black (see 35-430, 35-432, 35-449)
	35-437-BU	18	Pushbutton Caps--10 pack Red (see page 290)
	35-438-BU	18	Pushbutton Caps--10 pack Black (see page 290)
	35-758-BU	19	Magnet Only for 35-753-BU and 35-757-BU



Fig. 15



Fig. 17



Fig. 18



Fig. 19

CIRCUIT BREAKERS & SPECIALTY SWITCHES (Cont.)

