

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: SOLDER 60/40 ROSIN CORE**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product Type: Solder
Product Name: **SOLDER 60/40 ROSIN CORE**
Part Number(s): **6033, 6034, 6040, 6045
9132, 9134, H3-390, H3-391**

Emergency Contact: **Chemtrec**
Phone: **(800) 424-9300**

SECTION 2. HAZARDS IDENTIFICATION

Goods hazard classification: Reproductive toxicity Category 1
Carcinogenicity Category 2
Acute toxic substance (inhalation) Category 4

Indication content:
Symbol : Health \ Exclamation

Signal word : Hazard

Hazard statement :

1. May damage fertility or the unborn child
2. Suspected of causing cancer
3. Harmful if inhaled

Precautionary statements :

1. Use only with adequate ventilation
2. Dispose of surplus and container via a licensed waste disposal contractor
3. Get medical attention if accident or irritation occurs

Other hazard: —

SECTION 3. COMPOSITION, INFORMATION OR INGREDIENT

Mixture :

Components-Chemical Name	CAS number	Density or Scope of Density Percentage
Tin	7440-31-5	4.0-95
Lead	7439-92-1	5.0-98
Silver	07440-22-4	0-5.0
Rosin	8050-09-7	0.5-5.0

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: SOLDER 60/40 ROSIN CORE**SECTION 4. FIRST AID MEASURES**

First aid method in the different exposed way:	
EYE CONTACT	Gently rinse the affected eyes with clean water for at least 15 minutes. Arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.
SKINCONTACT	Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.
INHALATION	Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.
INGESTION	Give the person one or two glasses of water or solution of salt, try to get the victim to vomit. Arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.
The most important symptoms and hazardous effect: Irritation feeling	
The protection to first-aid: Should wear the level C protection equipment in the safe area implementation first aid.	
Notes to physicians: If the patient swallows, consideration gastric lavage and bowel movement.	

SECTION 5. FIRE-FIGHTING MEASURES

EXTINGUISH MEDIA:
Use alcohol resistant foam, carbon dioxide or dry chemical extinguishing agents.

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: SOLDER 60/40 ROSIN CORE**SECTION 5. FIRE-FIGHTING MEASURES (CONTINUED)****FIRE-FIGHTING INSTRUCTIONS:**

- Shut off fuel to fire if possible to do so without hazard.
- Evacuate area and fight fire from a safe distance.
- Apply water from a safe distance to cool and protect surrounding area.
- Firefighters should wear proper protective equipment.

FLASH POINT:_Not applicable**EXPLOSION LIMIT:**_Not available**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Shut out all sources of ignition; No flare, smoking or flames in area.

Wear proper protective equipment.

For spills, wipe and scrape away with cloth or paper, take up and store in a sealed container.

SECTION 7. HANDLING AND STORAGE**HANDLING:** Do not use fire near storage area.

Wear proper protective equipment.

STORAGE: Dry and non-corrosive with no sunlight**SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION****ENGINEERING MEASURES_**

Use only with adequate ventilation and in closed systems.

Make available emergency shower and eye wash in the work area.

ENGINEERING MEASURES :

Hazardous ingredient	TWA(mg/m3)	STEL	CEILING	BEIs
Lead	0.1	---	---	---
Tin	2.0	---	---	---

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: SOLDER 60/40 ROSIN CORE**SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION (CONTINUED)****PROTECTIVE EQUIPMENT:**

RESPIRATORY PROTECTION: Industrial canister gas masks. (Heating)

EYE PROTECTION: Safety goggles.

HAND, SKIN AND BODY PROTECTION: Rubber gloves.

Selection of specific items such as boots, apron or full-body suit will depend on operation.

SECTION 9. PHYSICS AND CHEMICAL PROPERTY

Appearance : Silver gray Solid	Odor : —
Odor threshold : —	Melting point : 183-316°C
Ph value : —	Boiling point : —
Flammability : —	Flash point : —
Decomposition temperature : —	Test method : —
Auto ignition temperature : —	Explosion limits : —
Vapor pressure : —	Vapor density : —
Density : 8.2-11.2 g/cm ³	Solubility : Almost Insoluble
Partition coefficient (log Kow) : —	Evaporation rate : —

SECTION 10. STABILITY AND REACTIVITY**CHEMICAL STABILITY:**

Stable, hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:

Strong oxidizing agents, strong bases and strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon oxide on burning.

HAZARDOUS POLYMERIZATION:

Will not occur.

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: SOLDER 60/40 ROSIN CORE

SECTION 11. TOXICOLOGICAL INFORMATION

CORROSIVE AND IRRITANT PROPERTIES: Not available
ALLERGENIC AND SENSITIZING EFFECTS: Not available
ACUTE TOXICITY: Not available
SUB-ACUTE TOXICITY: Not available
CHRONIC TOXICITY: Animal drink water containing 0.18mg/L of lead may get lead poisoning. Rats ingested the 0.005mg/Kg of lead showed evidence of CMS disturbances.
CARCINOGENIC EFFECTS: Not available
MUTAGENIC EFFECTS: Not available
EFFECTS ON THE REPRODUCTIVE SYSTEM: Not available
TERATOGENIC EFFECTS: Not available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: —
Persistent and biodegradable: —
Bio-accumulative potential: —
Mobility in soil: —
Other adverse effects: —

SECTION 13. DISPOSAL CONSIDERATIONS

Methods of waste disposal: Bury with qualified hygiene.
--

SECTION 14. TRANSPORT INFORMATION

UN No.: Not applicable
UN Proper shipping name: Not applicable
Transportation hazard classification : Not-restricted by IATA and IMDG. IMO- IMDG /ICAO/ IATA –DGR : NOT REGULATED AS A DANGEROUS.
Packing group: Not applicable
Marine pollutant (Yes/No): Not applicable
Specific transport measures and precautionary conditions: Dry and non-corrosive with no sunlight

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: SOLDER 60/40 ROSIN CORE

SECTION 15. REGULATORY INFORMATION

Applicable regulations:

1. Occupation safe hygiene facilities rule.
2. Laborer operating environment permits the thickness standard
3. Industrial waste storage cleaning dispose method and facility standard
4. Hazardous chemicals labeled general rule

SECTION 16. OTHER INFORMATION

Reference	Occupational Safety and Health Administration , Ministry Of Labor, GHS inquiry system
------------------	---

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of the information. Persons receiving information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.