



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

MSDS Number: 273
 Revision Date: 04/21/2015
 Supersedes Date: 08/07/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200



Product Name: ROSIN CORE SOLDER WIRE

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Type: Solder
 Product Name: **ROSIN CORE SOLDER WIRE**
 Part Number(s): ~~6056~~ Disc.
 6059

Emergency Contact: **Chemtrec**
 Phone: **(800) 424-9300**

SECTION 2: HAZARDS IDENTIFICATION

<p>Goods hazard classification: 1. Reproduction toxic substances Level 1 2. Lead: Carcinogenic substances Level 2 3. Acute toxic substance (inhalation) Level 4</p>
<p>Indication content:  </p> <p>Symbolic mark : Health - Exclamation mark</p> <p>Warnings: Hazard</p> <ol style="list-style-type: none"> 1. Contains material which may cause cancer 2. Contains material which may cause reproductive harms or birth defects 3. Toxic by inhalation <p>Measure : <ol style="list-style-type: none"> 1. Use only with adequate ventilation 2. Dispose of surplus and container via a licensed waste disposal contractor 3. Get medical attention if accident or irritation occurs </p> <p>Other hazard: —</p>

SECTION 3: COMPOSITION, INFORMATION OR INGREDIENT

Pure substances:

Components name:
Other name:
CAS No.:
Hazards composition (wt. %):



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

MSDS Number: 273
 Revision Date: 04/21/2015
 Supersedes Date: 08/07/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: ROSIN CORE SOLDER WIRE

SECTION 3: COMPOSITION, INFORMATION OR INGREDIENT (CONTINUED)

Mixture :

Components-Chemical Name :	(CAS No.) :	Hazards composition (wt. %):
Rosin	8050-09-7	1.0~4.0
Tin	7440-31-5	5~70
Silver	7440-22-4	0.0~5.0
Lead	7439-92-1	30~95

SECTION 4: FIRST AID MEASURES

First aid method in the different exposed way:	
EYE CONTACT	Gently rinse the affected eyes with clean water for at least 15 minutes. Arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.
SKINCONTACT	Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.
INHALATION	Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.
INGESTION	Give the person one or two glasses of water or solution of salt, try to get the victim to vomit. Arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.
The most important symptoms and hazardous effect: Irritation feeling	
The protection to first-aid: Should wear the level C protection equipment in the safe area implementation first aid.	
Notes to physicians: If the patient swallows, consideration gastric lavage and bowel movement.	



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 273
Revision Date: 04/21/2015
Supersedes Date: 08/07/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: ROSIN CORE SOLDER WIRE

SECTION 5: FIRE-FIGHTING MEASURES

EXTINGUISH MEDIA:

Use alcohol resistant foam, carbon dioxide or dry chemical extinguishing agents.

FIRE-FIGHTING INSTRUCTIONS:

- Shut off fuel to fire if possible to do so without hazard.
- Evacuate area and fight fire from a safe distance.
- Apply water from a safe distance to cool and protect surrounding area.
- Firefighters should wear proper protective equipment.

FLASH POINT: _Not applicable

EXPLOSION LIMIT: _Not available

SECTION 6: ACCIDENTAL RELEASE MEASURES

Shut out all sources of ignition; No flare, smoking or flames in area.

Wear proper protective equipment.

For spills, wipe and scrape away with cloth or paper, take up and store in a sealed container.

SECTION 7: HANDLING AND STORAGE

HANDLING: Do not use fire near storage area.
Wear proper protective equipment.

STORAGE: Keep away from heat or sunlight.

Store in a cool (0-10°C) place in closed containers.



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

MSDS Number: 273
 Revision Date: 04/21/2015
 Supersedes Date: 08/07/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: ROSIN CORE SOLDER WIRE

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING MEASURES_

Use only with adequate ventilation and in closed systems.
 Make available emergency shower and eye wash in the work area.

EXPOSURE GUIDELINES_

ACGIH TLV: 0.1mg/m3 (Lead)
 2.0mg/m3 (Tin)

PROTECTIVE EQUIPMENT:

RESPIRATORY PROTECTION:Industrial canister gas masks.(Heating)
 EYE PROTECTION:Safety goggles.
 HAND, SKIN AND BODY PROTECTION: Rubber gloves.
 Selection of specific items such as boots, apron or full-body suit will depend on operation.

SECTION 9: PHYSICS AND CHEMICAL PROPERTY

Appearance:	Gray colored paste
BOILING POINT	>200°C (Flux)
VAPOR PRESSURE:	<0.01mmHg(20°C)
MELTING POINT	179~183°C (Solder)
SPECIFIC GRAVITY	8.4g/cm3 (Solder, 20°C)
SOLUBILITY (IN WATER)	Almost Insoluble



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 273
Revision Date: 04/21/2015
Supersedes Date: 08/07/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: ROSIN CORE SOLDER WIRE

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY:

Stable, hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:

Strong oxidizing agents, strong bases and strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon oxide on burning.

HAZARDOUS POLYMERIZATION:

Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

CORROSIVE AND IRRITANT PROPERTIES:Not available

ALLERGENIC AND SENSITIZING EFFECTS:Not available

ACUTE TOXICITY:Not available

SUB-ACUTE TOXICITY:Not available

CHRONIC TOXICITY:Animal drink water containing 0.18mg/L of lead may get lead poisoning.

Rats ingested the 0.005mg/Kg of lead showed evidence of CMS disturbances.

CARCINOGENIC EFFECTS:Not available

MUTAGENIC EFFECTS:Not available

EFFECTS ON THE REPRODUCTIVE SYSTEM:Not available

TERATOGENIC EFFECTS:Not available

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: —

Persistent and biodegradable: —

Bio-accumulative potential: —

Mobility in soil: —

Other adverse effects: —



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

MSDS Number: 273
Revision Date: 04/21/2015
Supersedes Date: 08/07/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: ROSIN CORE SOLDER WIRE

SECTION 13: DISPOSAL CONSIDERATIONS

Methods of waste disposal: Bury with qualified hygiene.

SECTION 14: TRANSPORTS INFORMATION

UN No.: —

UN Proper shipping name: —

Transportation hazard classification: —

Packing group: —

Marine pollutant (Yes/No): —

Specific transport measures and precautionary conditions: —

SECTION 15: REGULATORY INFORMATION

Applicable regulations:

1. Occupation safe hygiene facilities rule.
2. Laborer operating environment permits the thickness standard
3. Industrial waste storage cleaning dispose method and facility standard
4. Hazardous chemicals labeled general rule

SECTION 16: OTHER INFORMATION

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of the information. Persons receiving information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.