

ACCESSORIES (Cont.)

Chem



Foam Applicators

6" Foam-tip applicator on polypropylene shaft.
Head size 3/16" D x 11/16" L.

Part No. 19-753 Package of 50



Cotton Applicators

6" Pointed cotton-tip applicator on wooden shaft. Head size @.105" D, tapering to .020" Dia.


Part No. 19-755
6" Single cotton-tip applicator on wood shaft. Package of 100.

Part No. 19-756
6" Pointed cotton-tip applicator on wood shaft. Package of 100.

Part No. 19-758
3" Cotton-tip applicator on wood Shaft. Package of 100.

Part No. 19-759
6" Double-tipped cotton applicator. Package of 100.

CIRCUIT BOARDS



Bare Copper Circuit Boards

One ounce copper (0.0014") on base of either FR-4 (G-10) fiberglass or CEM-1 type epoxy reinforced board, 1/16" thick.

Copper on **One Side Only**:

Part No. 22-250 3" x 5"

Part No. 22-261 6" x 6"

Part No. 22-263 6" x 9"

Part No. 22-264 8" x 10"

Part No. 22-268 11" x 14"




Positive Pre-Sensitized Phenolic Circuit Boards

Made of 1.5 mm (1/16") thick phenolic base with one ounce (0.0014") copper. Coated with POSITIVE photo etch resist. Use Developer concentrate.

Dielectric constant at 1 MHz=5.3.

Copper on **One Side Only**:

Part No. 21-169 6" x 9"



Positive Pre-Sensitized Circuit Boards

1 oz. copper (0.0014") on a 1/16" (UL 94V-O) epoxy-glass FR-4 board. New high quality positive pre-sensitized PC boards are double protected from light and handling damage. The peel-off coating protects the board while handling or cutting prior to exposure. Can be exposed with common fluorescent lamp. GC makes it easy for anyone to make a professional looking board. Use with Developer concentrate.

Dielectric constant at 1 MHz = 5.4

Meets Fed. Spec.: S-10941-1.

Copper on **Both Sides**:

Part No. 21-339
3" x 4"

Part No. 21-350
6" x 6"

Part No. 21-353
6" x 9"

Part No. 21-357
12" x 12"

Copper on **One Side Only**:

Part No. 21-332
3" x 4"

Part No. 21-243
3" x 6"

Part No. 21-334
4" x 6"

Part No. 21-336
6" x 6"

Part No. 21-247
7" x 10"