

## HEAD CLEANERS



### VCR/Magnetic Head Cleaner

VCR/Magnetic Head Cleaner removes dust, dirt and oxide from record and playback heads on VCR's, cassette decks and computer drives. Evaporates quickly and leaves no residue.

Environmental Data  
CFC: 0%, HCFC: 0%, Cl. Solv.: 0%,  
ODP: .0, VOC 100%

<b>Part No. 19-5302</b>	2 fl. oz. Non-Aerosol
	Replaces Part No. 10-5302
<b>Part No. 19-5302-G</b>	1 gal.
<b>Part No. 19-5304</b>	4 oz. Aerosol



### Travel Dispenser

Designed for easy one-handed delivery of a wide variety of liquids onto a cloth, cleaning pad, cotton ball or other wipe-on applicators. Can conveniently apply polishes, removers or other liquid products onto the applicator eliminating direct hand contact, spillage, fumes and waste while protecting product quality. The locking top makes this product excellent for use in the technicians tool box. This dispenser is available empty or prefilled with two of your favorite GC Chemicals; Head Cleaner or Isopropyl Alcohol.

<b>Part No. 19-770</b>	4 fl. oz. Isopropyl Alcohol
<b>Part No. 19-773</b>	4 fl. oz. VCR/Magnetic Head Cleaner
<b>Part No. 19-774</b>	4 fl. oz. Dispenser only

## LUBRICANTS



### White Lithium Grease

White, lithium soap base grease lubricant that provides superior lubrication and reduces friction and wear to a minimum. Suitable for use on wiping contacts. It retains consistency over a wide range of temperatures, will not oxidize or harden and provides outstanding protection against corrosion.

**Part No. 19-2302** 1 3/4 fl. oz. Tube



### Tunerlube

Special lubricant for high frequency contact applications such as television tuners. Purified without traces of metals or metal oxides. Gives lasting protection against oxidation and corrosion. Especially important for use on equipment operated in corrosive atmospheres such as seashores or in industrial areas.

**Part No. 10-2610** 1 3/4 fl. oz. Tube  
N.S.N. 9150-01-054-0546



### Anti-Oxidant Grease

A lithium soap base grease with zinc and graphite fillers. Use for wire connectors and aluminum conduit joints. Penetrates aluminum oxide to maintain inter-strand and inter-conductor current paths. Guards against oxidation, improves conductivity and produces a cooler connection.

**Part No. 19-826** 1 oz.  
Replaces Part No. 19-820



### Luberex

Superior calcium stearate base grease compound for general use in industry, the shop or at home. Provides excellent lubrication for bearings, appliances, hand tools, bicycles and other sporting equipment including fishing reels and guns; also for business machines, instruments and automotive lubrication. Excellent dielectric properties.

**Part No. 10-1206** 2 fl. oz. Tube



### Phonolube

Light bodied grease made of polymerized oil, specially developed for the lubrication of small geared mechanisms such as phonographs, record changers, TV channel and record mechanisms, etc. Retains its viscosity over a wide range of temperatures. Highly resistant to oxidation. Will retain its excellent lubricating qualities for years.

**Part No. 10-1223** 2 fl. oz. Tube



### Reach-All Pen Oiler

High quality, non-gumming instrument oil. Tube extends and retracts. Excellent for lubricating instruments, gears, timers, clocks, guns, fishing reels, and other densely mechanized items.

**Part No. 10-985** 1/2 fl. oz. Pen Type Cartridge  
Replaces Part No. **10-984**



### Graphite Lubricant

Dry powdered graphite is the finest lubricant for metal, wood, plastic, and rubber. (No solvents to harm plastics.) Guards against sticking and dirt build up. Reduces wear and corrosion. Ideal for many uses including locks, hinges, doors, wheels, and rubber parts.

**Part No. 19-821** 1 1/8 oz.



### Sili-Spray

Quality silicone lubricant. Handy aerosol features adjustable 3-way valve. Dispenses lubricating film either light, medium, or heavy according to need. Leaves no residue buildup. Ideal for home, office, workshop, hinges, slides, and other moving parts on automobiles, boats, appliances, toys and drawers (wooden types). May be painted over.

**Part No. 19-601** 4 oz. Aerosol



### Dry TFE

GC Dry TFE is an all purpose dry film lubricant and release agent that contains minute Teflon® particles to lubricate where a dry lubricant is needed. Excellent as a mold release and for potting compounds. Temperatures range: -300° F to +500° F. (Teflon is a registered trademark of Dupont.)

**Part No. 19-810** 4 oz. Aerosol