

SILICONE RUBBER ADHESIVE/SEALANT

A multi-purpose one-component elastomer sealant that cures to a tough, rubbery solid when exposed to moisture in the air. Because it does not flow, this sealant can be applied overhead or on sidewall joints and surfaces without sagging, slumping or running off. It typically adheres to clean metal, glass, most types of wood, silicone resin, vulcanized silicone rubber, ceramic, natural and synthetic fiber, painted surfaces and many plastic surfaces. It is designed to fulfill industrial and electronic service sealing and bonding requirements.

It has excellent adhesive strength, high elongation and outstanding insulation and heat resistance qualities. It may be applied in subzero weather without loss of extrusion or physical property characteristics.

FEATURES:

- Clear Color
- 550 v/mil Dielectric Strength
- 220 psi Tensile Strength
- Temp. Range (-80 to 400)°F
- 18 Months Shelf Life from D.o.M. (un-opened)

Product Availability:

PART No.	DESCRIPTION	SIZE
10-150	Silicone Rubber Clear	3 oz. Tube



UPC: 010151132550

HTS: 8536.90.4000

CoO: USA

PART No: **10-150**

INSTRUCTIONS:

Is supplied in ready-to-use form. It extrudes readily from its container under pressure.

The paste-like consistency makes it easy to work with. A spatula or paddle can be used to tool the surface.

CURE:

Cures tack free in 10 minutes with full cure in 24 hours.